

3RAA-031E-TAC

HFC, R-404A, 60Hz, 3- Phase, 208/230 V

Medium Temperature



Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	20 / 120	0 / 110
RG(°F)/Liq(°F)	65.0 / 120.0	65.0 / 110.0
Capacity (Btu/hr)	26200	17500
Power (Watts):	4240	3220
Current (Amps):	12.20	9.70
EER (Btu/Wh):	6.20	5.40
Mass Flow (lbs/hr):	550	329
Sound Power (dBA):		
Vibration (mils(peak-peak)):		
Record Date:	2006-08-03	

Mechanical

Number of Cylinders:	2	Displ(in ³ /Rev):	10.34
Bore Size(in):	2.19	Displ(ft ³ /hr):	628.28
Stroke(in):	1.38		
Overall Length (in):	18.63	Mounting Length (in):	11.63
Overall Width (in):	13.00	Mounting Width (in):	11.00
Overall Height (in):	12.78	Mounting Height (in):	13.81 *
Suction Size (in):		1 1/8 Sweat	
Discharge Size (in):		5/8 Flare	
Oil Recharge (oz):		65	
Initial Oil Charge (oz):		70	
Net Weight (lbs):		178	
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	82.0	MCC (Amps):	19.8	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	10-Sep-1984
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		14.1			
RLA(=MCC/1.56;use for breaker & wire size selection):		12.7			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	200/220	UL Medium Temp
R-404A HFC	50	3	200/220	Medium Temperature
R-507 HFC	50	3	200/220	
R-22 HCFC	60	3	208/230	UL Medium Temp
R-507 HFC	60	3	208/230	