

RS97C2E-CAA

HFC, R-404A, 60Hz, 1- Phase, 115 V
Extended Medium Temp



Production Status: This model is obsolete and is no longer in production for both OEM and service replacement. Please contact Customer Service about possible replacement models.

Performance

Evap(°F)/Cond(°F)	20 / 120	-10 / 120
RG(°F)/Liq(°F)	40.0 / 120.0	40.0 / 120.0
Capacity (Btu/hr)	9080	3620
Power (Watts):	1910	1230
Current (Amps):	18.80	14.00
EER (Btu/Wh):	4.70	2.90
Mass Flow (lbs/hr):	217	83
Sound Power (dBA):	0 Avg	0 Max
Vibration (mils(peak-peak)):	0.0 Avg	0.0 Max
Record Date:	2004-09-09	

Mechanical

Number of Cylinders:	1	Displ(in ³ /Rev):	2.02
Bore Size(in):	1.69	Displ(ft ³ /hr):	245.34
Stroke(in):	0.90		
Overall Length (in):	11.12	Mounting Length (in):	8.00
Overall Width (in):	6.62	Mounting Width (in):	4.81
Overall Height (in):	10.75	Mounting Height (in):	11.00 *
Suction Size (in):	1/2 Stub		
Discharge Size (in):	3/8 Stub		
Oil Recharge (oz):	20		
Initial Oil Charge (oz):	24		
Net Weight (lbs):	52		
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	95.0	MCC (Amps):	29.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	23-Jun-1972
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		20.7			
RLA(=MCC/1.56;use for breaker & wire size selection):		18.6			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
--------------------	------------------	--------------	----------------	--------------------