

RESCUE® Motors Permanent Split Capacitor Condenser Fan

5.6" Diameter, Totally Enclosed Air Over (TEAO)




APPLICATIONS:

Commercial and Residential Condensing Units. Can replace a range of horsepower application and a variety of mounting styles.

FEATURES:

- High 158°F (70°C) Or 140°F (60°C) Ambient Designs
- Automatic Reset Thermal Overload Protector
- Designed For Use With 370V Capacitors
- Special Treated Rotor For Corrosion Protection
- Includes Lead End Mounting Holes For Rheem® or Trane® Units
- 48" Leads
- Extended Mounting Studs
- Ball Bearings
- Reversible Rotation
- High Efficiency Design
- Continuous Duty, Air Over
- Reversible Rotation
- **Discount Symbol: DS-3HAC**



RESCUE® Condenser Motors
available in 158°F (70°C)
ambient ratings!

HP	RPM	Volts	Catalog Number	List	Max. Ambient	Speed Tap (RPM)	Cap. MFD @ 208V	Cap. MFD @ 230V	Amps	Shaft N	Shell XI	Total C	Ship Wgt.	Notes
1/3	825	208-230	5464	\$182	140°F(60°C)	High (825)	10	7.5	1.9	5	5.3	10.3	18	H43
1/4						High (835)	10	7.5	1.5					
1/5						Low (825)	10	7.5	1.2					
1/6						Low (825)	10	7.5	1.0					
1/3	825	208-230	5464H	\$186	158°F(70°C)	High (825)	10	7.5	1.9	5	5.3	10.3	18	H43
1/4						High (835)	10	7.5	1.5					
1/5						Low (825)	10	7.5	1.2					
1/6						Low (835)	10	7.5	1.0					
1/3	1075	208-230	5462	\$140	140°F(60°C)	High (1110)	7.5	5	2.6	5	4.6	9.6	14	H43
1/4						High (1135)	7.5	5	2.5					
1/5						Low (1110)	7.5	5	2.0					
1/6						Low (1125)	7.5	5	1.8					
1/3	1075	208-230	5462H	\$153	158°F(70°C)	High (1110)	7.5	5	2.6	5	4.6	9.6	14	H43
1/4						High (1135)	7.5	5	2.5					
1/5						Low (1110)	7.5	5	2.0					
1/6						Low (1125)	7.5	5	1.8					
1/2	1075	208-230	5465	\$177	140°F(60°C)	High (1110)	12.5	10	3.0	5	5.3	10.3	19	H43
1/3						High (1135)	12.5	10	2.2					
1/4						Low (1110)	12.5	10	1.6					
1/6						Low (1125)	12.5	10	1.3					
1/2	1075	208-230	5465H	\$190	158°F(70°C)	High (1110)	12.5	10	3	5	5.3	10.3		H43
1/3						High (1135)	12.5	10	2.2					
1/4						Low (1110)	12.5	10	1.6					
1/6						Low (1125)	12.5	10	1.3					
3/4	1075	208-230	5482H	\$205	158°F(70°C)	High (1115)	15	15	4	5	6.3	11.875		H43
1/2						High (1145)	15	15	2.8					
1/3						Low (1115)	15	15	1.9					
1/4						Low (1145)	15	15	1.4					

460 Volt Rescue Condenser Fan Motors

HP	RPM	Volts	Catalog Number	List	Max. Ambient	Speed Tap (RPM)	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wgt.	Notes
1/2	1075	460	5480H	\$308	158°F(70°C)	High (1095)	10	1.3	5	5.562	11.1	19	H43
1/3						High (1145)	10	0.9					
1/4						Low (1100)	10	0.7					
1/5						Low (1140)	10	0.5					
1/6						Low (1150)	10	0.5					
3/4	1075	460	5481H	\$333	158°F(70°C)	High (105)	15	2.2	5	6.3	11.857	22	H43
1/2						High (1135)	15	1.3					
1/3						Low (1070)	15	1.1					
1/4						Low (1130)	15	0.7					

Note H43 Side Shell & Lead End Mounting Screws Included In Carton

† All marks shown within this document are properties of their respective owners



DRIVES
BRAKE
MOTORS
GENERAL PURPOSE
SINGLE PHASE
HVAC
WASHDOWN
AGRICULTURE
COMMERCIAL PUMP
MOTORS
CLOSE COUPLED
PUMP MOTORS
FIRE PUMP
MOTORS
POOL & SPA
MOTORS
RESIDENTIAL
WATER PUMP
ELEVATOR AND
GATE & DOOR